

ULTRACUT® 370 Plus

General purpose, semi-synthetic cutting and grinding fluid

Applications

ROCOL® ULTRACUT 370 Plus is a high dilution, semi-synthetic, general purpose, water mix cutting and grinding fluid formulated to give a long and predictable sump life with inherent resistance to degradation.

ULTRACUT 370 Plus is formulated to provide optimum performance at high dilutions on a wide range of ferrous and non-ferrous metals.

The versatility of ULTRACUT 370 Plus enables the user to rationalise to one fluid for both cutting and grinding operations.

ULTRACUT 370 Plus forms a translucent green micro-emulsion when mixed with water which provides a clear view of the workpiece.

Features and Benefits

- ULTRACUT 370 Plus is a multipurpose cutting and grinding fluid.
- Compatible with both hard and soft water.
- High dilutions providing low in sump costs.
- ULTRACUT 370 Plus is suitable for use with most materials.
- Excellent residual corrosion protection.
- Inherently resistant to degradation.
- Tolerant to tramp oil.
- Low foaming.
- Pleasant and safe to use

Usage Guidance

- ULTRACUT 370 Plus should be used between 40:1 and 60:1 for cutting and between 50:1 and 70:1 for grinding depending on the severity of operation, workpiece material and water hardness.
- To ensure dilution accuracy, it is preferable to use a ROCOL Automatic Fluid Mixer. For manual mixing, add the concentrate to the water at the recommended dilution ratio, stirring continuously.
- It is advisable to use the appropriate ROCOL ULTRAGUARD® Machine Tool Care product at fluid changeovers. Optimum fluid life is obtained by adequate initial machine cleaning, correct dilution control and regular maintenance of the fluid, particularly prior to weekends and shutdown periods.

Storage Guidance

- ULTRACUT 370 Plus should be stored in a cool, well ventilated area, between +5°C and +30°C, in the original container.
- If stored in accordance with the above guidelines, shelf life is 1 year from date of manufacture.

Pack Sizes

Part Code	Pack Size
51376	5L
51373	20L
51379	200L
51375	1000L

T +44 (0) 113 232 2600
E customer.service@rocol.com

www.rocol.com

ROCOL A Division of ITW Limited
ROCOL House, Swillington, Leeds, LS26 8BS, UK
VAT Number: 742053167
Registered Company No: 00559693
Registered Office: Saxon House, 2-4 Victoria Street, Windsor, England, SL4 1EN



ULTRACUT® 370 Plus

General purpose, semi-synthetic cutting and grinding fluid

Parameter	Test Method	Value
Appearance:		
Concentrate	N/A	Green liquid
Mixed with water	N/A	Translucent green emulsion
Odour	N/A	Mild
pH	N/A	9.5 at 15:1 dilution
Density at 20 °C (g/cm ³)	N/A	1.00

Refractometer Calibration

Dilution Ratio	30:1	40:1	50:1	60:1	70:1	80:1
Refractometer Reading	2.1	1.6	1.3	1.1	0.9	0.8

Safety Datasheets

These are available at <https://www.rocol.com/datasheets>. For further assistance, please contact us via the ROCOL website or using the details below.

Note

The information in this Technical Datasheet is informed by our experience and feedback from industry. There are many variables outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility. Values quoted are typical and do not constitute a specification.

If you'd like to discuss the suitability of any ROCOL solution for your system, please get in touch.

T +44 (0) 113 232 2600
E customer.service@rocol.com

www.rocol.com



ROCOL A Division of ITW Limited
ROCOL House, Swillington, Leeds, LS26 8BS, UK
VAT Number: 742053167
Registered Company No: 00559693
Registered Office: Saxon House, 2-4 Victoria Street, Windsor, England, SL4 1EN

Revision Date: 0826

Template: 2507

